Zn / MnO2

MICROPOWER ZINC-CARBON BATTERY

Size: C / R14, 1.5V

Dimensions(GB):
49.5±0.5mm × ø25.5±0.5mm

Dimensions(GB)

PHYSICAL CHARACTERISTICS

- ChemicalSystem Zn/ ZnCl2-NH4Cl-H2O/MnO2
- Typical weight 40g
- Jacket PVC Label
- Heavy Metal Contents 0% Hg & Cd
- Reference document: IEC60086-1,-2,- 5: 2015，GB/T8897. 1.2-2013，GB8897.5-2013

KEY FEATURES

- Which is Environmental Friendly
- Super Long Lasting Power
- Excellent Leakproof, as a result of pure material
- Extra Long Life Span
- Exel working in low temperature or high-drain discharging

OPERATING & STORAGE CONDITIONS

- Operating temperature range -20°C to 54°C
- Recommended Storage (storage area should be clean, cool, dry, and ventilated) 5°C to 30°C

CERTIFICATES

- CE
- IEC60086
- RoHS
- MSDS
- KC
- Air Transportation Certificate
- Sea Transportation Certificate

TYPICAL APPLICATIONS

- Medical Devices
- Industrial Devices
- Infrastructure Devices
- Life Safety Devices

This data is subject to change. Performance information is typical. Contact Us for the latest information.

Microcell International Battery Co., Ltd.

Phone: +86-512-67610171 / +86-15952405898
Email: sales3@micropowerbattery.com
Website: www.micropower-battery.com